



**ARIZONA PL**

**Specifications** June 13, 2025

<b>COUNTRY OF ORIGIN</b>	China		
<b>PERFORMANCE FINISH</b>	NO		
<b>FIBER CONTENT</b>	OVERALL	100%POLYE	
	FACE	100%POLYE	
	BACK	100%POLYE	
<b>CONSTRUCTION</b>	175 Ends Per Inch	76 Picks Per Inch	
<b>WIDTH</b>	54"		
<b>WEIGHT</b>	Approx. 1.070 lbs. per linear yard		
<b>RAILROADED</b>	Y		
<b>PATTERN REPEAT</b>	WARP N/A"	FILL N/A"	

**Performance** Standards

<b>SEAM BREAKING STRENGTH</b>	WARP/FILL	87/80 lbs	ASTM D-4034   MIN. 50 LBS
<b>TEAR STRENGTH</b>	WARP/FILL	15/13 lbs	ASTM D-2261-13   MIN. 6 LBS
<b>SEAM SLIPPAGE</b>	WARP/FILL	64/49 lbs	ASTM D-4034   MIN. 25 LBS
<b>TENSILE STRENGTH</b>	WARP/FILL	193/80 lbs	ASTM D-5034   MIN. 50 LBS
<b>ABRASION</b>	Heavy Duty – 15,000 Cycles (Wyzenbeck - Wire Screen Abradant)		ASTM D-4157   MIN. 9000 CYCLES
<b>PILLING</b>	Class 4		ASTM D-3511   MIN. CLASS 3
<b>UFAC</b>	Class I		
<b>CALIFORNIA TECHNICAL BULLETIN 117-2013</b>	Pass		PASS or FAIL
<b>COLORFASTNESS TO LIGHT</b>	40 Hours – Class 4		AATCC-16A   CLASS 3 or ABOVE
<b>COLORFASTNESS TO CROCKING</b>	DRY – Class 4.5 WET – Class 4.5		AATCC-8   MIN. CLASS 4.0 (DRY), CLASS 3.0 (WET)
<b>DYNAMIC SEAM FATIGUE</b>	Pass 5,000 Cycles		ASTM D-4033

\*Culp pattern test results are compliant to listed Fabric Standards and referenced testing methods.

Cleaning Code **W** - Spot clean only with water based shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not overwet. Do not use solvents to spot clean. Pile fabrics may require brushing with a non-metallic, stiff bristle brush to restore appearance. Hot water extraction or steam cleaning is not a recommended cleaning method. Cushion covers should not be removed and laundered. To prevent overall soiling, frequent vacuuming or light brushing with a non metallic, stiff bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling. Use a professional furniture cleaning service when an overall soiled condition has been reached.