

# DOLABRA

## Specifications

June 03, 2025

|                    |                                    |                            |
|--------------------|------------------------------------|----------------------------|
| COUNTRY OF ORIGIN  | China                              |                            |
| PERFORMANCE FINISH | NO                                 |                            |
| FIBER CONTENT      | OVERALL                            | 72%POLYE23%RYN3%LINEN2%ACR |
|                    | FACE                               | N/A                        |
|                    | BACK                               | N/A                        |
| CONSTRUCTION       | 81 Ends Per Inch                   | 38 Picks Per Inch          |
| WIDTH              | 54"                                |                            |
| WEIGHT             | Approx. 1.430 lbs. per linear yard |                            |
| RAILROADED         | Y                                  |                            |
| PATTERN REPEAT     | WARP 6.97"                         | FILL 17.72"                |

## Performance

## Standards

|                                               |                                                                  |             |                                                 |
|-----------------------------------------------|------------------------------------------------------------------|-------------|-------------------------------------------------|
| <b>SEAM BREAKING STRENGTH</b>                 | WARP/FILL                                                        | 85/90 lbs   | ASTM D-4034   MIN. 50 LBS                       |
| <b>TEAR STRENGTH</b>                          | WARP/FILL                                                        | 34/46 lbs   | ASTM D-2261-13   MIN. 6 LBS                     |
| <b>SEAM SLIPPAGE</b>                          | WARP/FILL                                                        | 66/38 lbs   | ASTM D-4034   MIN. 25 LBS                       |
| <b>TENSILE STRENGTH</b>                       | WARP/FILL                                                        | 246/136 lbs | ASTM D-5034   MIN. 50 LBS                       |
| <b>ABRASION</b>                               | Heavy Duty – 15,000 Cycles<br>(Wyzenbeck - Wire Screen Abradant) |             | ASTM D-4157   MIN. 9000 CYCLES                  |
| <b>PILLING</b>                                | Class 4                                                          |             | ASTM D-3511   MIN. CLASS 3                      |
| <b>UFAC</b>                                   | Class I                                                          |             |                                                 |
| <b>CALIFORNIA TECHNICAL BULLETIN 117-2013</b> | Pass                                                             |             | PASS or FAIL                                    |
| <b>COLORFASTNESS TO LIGHT</b>                 | 40 Hours – Class 4                                               |             | AATCC-16A   CLASS 3 or ABOVE                    |
| <b>COLORFASTNESS TO CROCKING</b>              | DRY – Class 4.0<br>WET – Class 4.0                               |             | AATCC-8   MIN. CLASS 4.0 (DRY), CLASS 3.0 (WET) |
| <b>DYNAMIC SEAM FATIGUE</b>                   | Pass 5,000 Cycles                                                |             | ASTM D-4033                                     |

\*Culp pattern test results are compliant to listed Fabric Standards and referenced testing methods.

Cleaning Code **W** - Spot clean only with water based shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not overwet. Do not use solvents to spot clean. Pile fabrics may require brushing with a non-metallic, stiff bristle brush to restore appearance. Hot water extraction or steam cleaning is not a recommended cleaning method. Cushion covers should not be removed and laundered. To prevent overall soiling, frequent vacuuming or light brushing with a non metallic, stiff bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling. Use a professional furniture cleaning service when an overall soiled condition has been reached.