



RHYMER

Specifications

June 30, 2025

| | | | |
|---------------------------|------------------------------------|-------------------|--|
| COUNTRY OF ORIGIN | China | | |
| PERFORMANCE FINISH | NO | | |
| FIBER CONTENT | OVERALL | 98%POLYE2%ACR | |
| | FACE | N/A | |
| | BACK | N/A | |
| CONSTRUCTION | 83 Ends Per Inch | 25 Picks Per Inch | |
| WIDTH | 54" | | |
| WEIGHT | Approx. 1.985 lbs. per linear yard | | |
| RAILROADED | Y | | |
| PATTERN REPEAT | WARP N/A" | FILL N/A" | |

Performance

Standards

| | | | |
|---|--|-------------|---|
| SEAM BREAKING STRENGTH | WARP/FILL | 91/82 lbs | ASTM D-4034 MIN. 50 LBS |
| TEAR STRENGTH | WARP/FILL | 55/111 lbs | ASTM D-2261-13 MIN. 6 LBS |
| SEAM SLIPPAGE | WARP/FILL | 49/61 lbs | ASTM D-4034 MIN. 25 LBS |
| TENSILE STRENGTH | WARP/FILL | 168/347 lbs | ASTM D-5034 MIN. 50 LBS |
| ABRASION | Heavy Duty – 15,000 Cycles (Wyzenbeck - Wire Screen Abradant) | | ASTM D-4157 MIN. 9000 CYCLES |
| PILLING | Class 4 | | ASTM D-3511 MIN. CLASS 3 |
| UFAC | Class I | | |
| CALIFORNIA TECHNICAL BULLETIN 117-2013 | Pass | | PASS or FAIL |
| COLORFASTNESS TO LIGHT | 40 Hours – Class 4 | | AATCC-16A CLASS 3 or ABOVE |
| COLORFASTNESS TO CROCKING | DRY – Class 4.0 WET – Class 4.0 | | AATCC-8 MIN. CLASS 4.0 (DRY), CLASS 3.0 (WET) |
| DYNAMIC SEAM FATIGUE | Pass 5,000 Cycles | | ASTM D-4033 |

*Culp pattern test results are compliant to listed Fabric Standards and referenced testing methods.

Cleaning Code **W** - Spot clean only with water based shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not overwet. Do not use solvents to spot clean. Pile fabrics may require brushing with a non-metallic, stiff bristle brush to restore appearance. Hot water extraction or steam cleaning is not a recommended cleaning method. Cushion covers should not be removed and laundered. To prevent overall soiling, frequent vacuuming or light brushing with a non metallic, stiff bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling. Use a professional furniture cleaning service when an overall soiled condition has been reached.